

Radial fan made of plastic, Direct drive

single inlet, for exhaust air, for continuous operation, welded, self-supporting casing optionally made of PP / PPs / PPs-el / PE / PVC / PVDF, splinter protection for maximum safety, round pipe connection for sleeve on inlet side, square flange on discharge side, Impeller with forward-curved blades optionally made of PP / PPs / PPs-el / PVDF, power transmission via standardize taper lock clamping bushing or form-fit, sturdy sheet steel construction optionally in galvanized / VA design, to accommodate casing and motor, three-phase motor outside the air stream

Fan

Casing material	<input type="checkbox"/> PP, <input type="checkbox"/> PPs, <input type="checkbox"/> PPs-el, <input type="checkbox"/> PVDF, <input type="checkbox"/> PE, <input type="checkbox"/> PVC
Impeller material	<input type="checkbox"/> PP, <input type="checkbox"/> PPs, <input type="checkbox"/> PPs-el, <input type="checkbox"/> PVDF
Casing orientation	LG / RD
Inlet diameter mm
Drive type	direct drive
Air flow m ³ /h
Static pressure Pa
Temperature °C
Sound pressure at 3m dB(A)
Operating impeller speed min ⁻¹
Efficiency stat. mech. %
Shaft power kW
Ex-Execution	<input type="checkbox"/>
Ex-Zone inside	Zone ... / Cat. ...
Ex-Zone outside	Zone ... / Cat. ...
Droplets excluded	<input type="checkbox"/> Yes / <input type="checkbox"/> No

Motor

Speed min ⁻¹
Power kW
Rated current A
Voltage V
Line frequency Hz
Safety class	IP ...
PTC resistor
Motor type
Ex-Execution	Ex ...

Fan weight kg
Motor weight kg
Total weight kg

Options/Accessories

Support execution	<input type="checkbox"/> galvanized, <input type="checkbox"/> V2A 1.4301 304, <input type="checkbox"/> V4A 1.4404 316
Required	<input type="checkbox"/> Vibration absorbers for floor mounting, <input type="checkbox"/> Isolation switch, <input type="checkbox"/> Sleeves or <input type="checkbox"/> protective grid
Optional	<input type="checkbox"/> Drain, <input type="checkbox"/> Frequency converter, <input type="checkbox"/> Motor cover, <input type="checkbox"/> Hub seal,

Edition 2023 • subject to alterations • Copyright by COLASIT AG Spiez

COLASIT AG

Plastic construction • Faulenbachweg 63 • CH-3700 Spiez
Tel. +41 (0)33 655 61 61 • fans@colasit.com

www.colasit.com

Competence in plastics. Worldwide.



Radial fan made of plastic, V-belt drive

single inlet, for exhaust air, for continuous operation, welded self-supporting casing optionally made of PP / PPs / PPs-el / PE / PVC / PVDF, splinter protection for maximum safety, round pipe connection on inlet side for sleeve, square flange on discharge side, impeller with forward-curved blades optionally made of PP / PPs / PPs-el / PVDF, Power transmission via standardized taper lock tension bush or form-fit, pedestal bearing units, V-belt pulleys with taper lock tension bushes, sturdy sheet steel construction optionally in galvanized / VA design, to accommodate casing, motor and the complete belt drive, belt guard, three-phase motor outside the air stream

Fan

Casing material	<input type="checkbox"/> PP, <input type="checkbox"/> PPs, <input type="checkbox"/> PPs-el, <input type="checkbox"/> PVDF, <input type="checkbox"/> PE, <input type="checkbox"/> PVC
Impeller material	<input type="checkbox"/> PP, <input type="checkbox"/> PPs, <input type="checkbox"/> PPs-el, <input type="checkbox"/> PVDF
Casing orientation	LG / RD
Inlet diameter mm
Drive type	V-belt drive
Air flow m ³ /h
Static pressure Pa
Temperature °C
Sound pressure at 3m dB(A)
Operating impeller speed min ⁻¹
Efficiency stat. mech. %
Shaft power kW
Ex-Execution	<input type="checkbox"/>
Ex-Zone inside	Zone ... / Cat. ...
Ex-Zone outside	Zone ... / Cat. ...
Droplets excluded	<input type="checkbox"/> Yes / <input type="checkbox"/> No

Motor

Speed min ⁻¹
Power kW
Rated current A
Voltage V
Line frequency Hz
Safety class	IP ...
PTC resistor
Motor type
Ex-Execution	Ex ...

Fan weight kg
Motor weight kg
Total weight kg

Options/Accessories

Support execution	<input type="checkbox"/> galvanized, <input type="checkbox"/> V2A 1.4301 304, <input type="checkbox"/> V4A 1.4404 316
Required	<input type="checkbox"/> Vibration absorbers for floor mounting, <input type="checkbox"/> Isolation switch, <input type="checkbox"/> Sleeves or <input type="checkbox"/> protective grid
Optional	<input type="checkbox"/> Drain, <input type="checkbox"/> Frequency converter, <input type="checkbox"/> Motor cover, <input type="checkbox"/> Hub seal,

Edition 2023 • subject to alterations • Copyright by COLASIT AG Spiez

COLASIT AG

Plastic construction • Faulenbachweg 63 • CH-3700 Spiez
Tel. +41 (0)33 655 61 61 • fans@colasit.com

www.colasit.com

Competence in plastics. Worldwide.

