

**Execution** Completely made of corrosion-free plastics for chemically corrosive exhaust air and gases.

**Application** Exhaust air pre-cleaning of tanks and vessels with chemically corrosive liquids due to " tank-vessel breathing" during filling processes as well as pressure and temperature fluctuations.

## Type 125



## Type 200



### Technical data

Airflow: 40-100m<sup>3</sup>/h  
 Water: ca. 4l/min bei 4bar  
 Pressure loss: 290Pa bei 40m<sup>3</sup>/h  
 370Pa bei 60m<sup>3</sup>/h  
 630Pa bei 80m<sup>3</sup>/h  
 990Pa bei 100 m<sup>3</sup>/h

Raw gas ON: DN65  
 Pure gas OFF: DN65  
 Fresh water ON: DN25/IG1/2"  
 Sewage water OFF: DN32

### Technical data

Airflow: 100-200m<sup>3</sup>/h  
 Water: ca. 10l/min bei 4bar  
 Pressure loss: 410Pa bei 100m<sup>3</sup>/h  
 370Pa bei 150m<sup>3</sup>/h  
 870Pa bei 200m<sup>3</sup>/h

Raw gas ON: DN100  
 Pure gas OFF: DN100  
 Fresh water ON: DN25/IG1/2"  
 Sewage water OFF: DN32



Execution also in ATEX Zones 1+2 available

The chemically contaminated discharge air that escapes during the filling of a storage tank is cleaned by the pre-scrubber, dehumidified and passed on in this way.

### Your advantages

- Completely made of high-quality chemical-resistant plastic
- Transparent for visual inspection
- Easy to clean
- Long service life
- Requires little maintenance

Edition 2023 • Subject to alteration • Copyright by COLASIT AG Spiez

#### COLASIT AG

Plastic construction • Faulenbachweg 63 • CH-3700 Spiez  
 Phone +41 (0)33 655 61 61 • plants@colasit.com

www.colasit.com

Competence in plastics. Worldwide.

