

**Execution** Completely made of corrosion-free plastics for chemically corrosive exhaust air and gases.

**Application** Exhaust air pre-cleaning of tanks and vessels with chemically corrosive liquids due to " tank-vessel breathing" during filling processes as well as pressure and temperature fluctuations.

Type 125



Type 200



## Technical data

Airflow:	40-100m <sup>3</sup> /h
Water:	approx. 4l/min at 4bar
Pressure loss:	290Pa at 40m <sup>3</sup> /h 370Pa at 60m <sup>3</sup> /h 630Pa at 80m <sup>3</sup> /h 990Pa at 100 m <sup>3</sup> /h
Raw gas	ON: DN65
Pure gas	OFF: DN65
Fresh water	ON: DN25/IG1/2"
Sewage water	OFF: DN32

## Technical data

Airflow:	100-200m <sup>3</sup> /h
Water:	approx. 10l/min at 4bar
Pressure loss:	410Pa at 100m <sup>3</sup> /h 370Pa at 150m <sup>3</sup> /h 870Pa at 200m <sup>3</sup> /h
Raw gas	ON: DN100
Pure gas	OFF: DN100
Fresh water	ON: DN25/IG1/2"
Sewage water	OFF: DN32



Execution also in ATEX Zones 1+2 available

The chemically contaminated discharge air that escapes during the filling of a storage tank is cleaned by the pre-scrubber, dehumidified and passed on in this way.

## Your advantages

- Completely made of high-quality chemical-resistant plastic
- Transparent for visual inspection
- Easy to clean
- Long service life
- Requires little maintenance